

CERAMIC TRIMMER CAPACITOR – 5mm

◆ Specifications

- Operating Temperature Range : -30°C to +85°C
- Rated Working Voltage : 100VDC
- Withstanding Voltage : 400VDC
- Insulation Resistance : 10⁴ MΩ min.
- Rotation Torque : 35 ~ 200 g-cm
- Soldering Temperature : 260±5°C

◆ Ratings

PART NO.	MIN. CAP. (pF)	MAX. CAP. (pF)	TEMP. COEFF. PPM/°C	Q Value	
				10Mhz	100MHz
CVNN05-030	1.3±50%	3.0 ⁺¹⁰⁰ / ₋₀ %	0±200	>300	>200
CVNN05-050	2.0±50%	5.0 ⁺¹⁰⁰ / ₋₀ %	-500±300	>300	
CVNN05-100	4.0±50%	10.0 ⁺¹⁰⁰ / ₋₀ %	-500±300	>300	
CVNN05-200	6.0±50%	20.0 ⁺¹⁰⁰ / ₋₀ %	-1000±600	>300	
CVNN05-300	7.0±50%	30.0 ⁺¹⁰⁰ / ₋₀ %	-1000±600	>250	
CVNN05-400	8.0±50%	40.0 ⁺¹⁰⁰ / ₋₀ %	-1600±800	>200	
CVNN05-500	9.0±50%	50.0 ⁺¹⁰⁰ / ₋₀ %	-1600±800	>200	
CVNN05-600	10.5±50%	60.0 ⁺¹⁰⁰ / ₋₀ %	-1600±800	>200	
CVNN05-700	13.0±50%	70.0 ⁺¹⁰⁰ / ₋₀ %	N1200±500	200min.	
CVNN05-900	15.0±50%	90.0 ⁺¹⁰⁰ / ₋₀ %	N1200±500	200min.	

◆ Drawing

NORMAL TYPE

